



SAFETY DATA SHEET
Jangro - POLYURETHANE FLOOR SEAL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Jangro - POLYURETHANE FLOOR SEAL
Product number A027 JA
Internal identification BD122-5

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Floor seal.

1.3. Details of the supplier of the safety data sheet

Supplier Jangro Limited
Jangro House
Worsley Road
Farnworth
Bolton. UK
BL4 9LU
Tel: 0845 458 5223
Fax: 01204 579 499
centraloffice@jangrohq.net

1.4. Emergency telephone number

Emergency telephone 01772 318 818 - 8.30am to 4.45pm - Mon to Fri

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards

Flam. Liq. 3 - H226

Health hazards

STOT SE 3 - H336

Environmental hazards

Not Classified

Classification (67/548/EEC or 1999/45/EC)

R10,R66,R67.

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

Jangro - POLYURETHANE FLOOR SEAL

Precautionary statements

- P102 Keep out of reach of children.
- P271 Use only outdoors or in a well-ventilated area.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P301 IF SWALLOWED:
- P313 Get medical advice/attention.
- P302+P352 IF ON SKIN: Wash with plenty of water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P315 Get immediate medical advice/attention.
- P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P501 Dispose of contents/container in accordance with local regulations.
- P261 Avoid breathing vapours.

Supplemental label information

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains

LOW AROMATIC WHITE SPIRIT

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

LOW AROMATIC WHITE SPIRIT	30-60%
CAS number: — EC number: 919-857-5 REACH registration number: 01-2119463258-33-xxxx	
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Liq. 3 - H226	Xn;R65. R10,R66,R67.
STOT SE 3 - H336	
Asp. Tox. 1 - H304	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation

Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Ingestion

Do not induce vomiting. Give plenty of water to drink. Get medical attention if any discomfort continues.

Skin contact

Wash with plenty of water.

Eye contact

Rinse immediately with plenty of water. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation

Vapours may cause drowsiness and dizziness.

Ingestion

No specific symptoms known. But - May cause discomfort if swallowed.

Jangro - POLYURETHANE FLOOR SEAL

Skin contact

No specific symptoms known. But prolonged or excessively repeated skin contact could lead to removal of natural oils from skin.

Eye contact

No specific symptoms known. Prolonged contact may cause redness and/or tearing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Extinguish with the following media: Foam, carbon dioxide or dry powder.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards

Thermal decomposition or combustion products may include the following substances: Irritating gases or vapours. May explode when heated or when exposed to flames or sparks.

5.3. Advice for firefighters

Special protective equipment for firefighters

Keep containers cool by spraying with water to reduce explosion risks. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and contact with skin and eyes.

6.2. Environmental precautions

Environmental precautions

Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Contain spillage with sand, earth or other suitable non-combustible material. Collect and place in suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Eliminate all sources of ignition. Avoid contact with skin and eyes. Avoid inhalation of vapours. Provide adequate ventilation.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Keep away from heat, sparks and open flame.

Jangro - POLYURETHANE FLOOR SEAL

7.3. Specific end use(s)

Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

Usage description

See Product Information Sheet & Label for detailed use of this product.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

LOW AROMATIC WHITE SPIRIT

Long-term exposure limit (8-hour TWA): WEL 150 ppm 1000 mg/m³

WEL = Workplace Exposure Limit

8.2. Exposure controls

Appropriate engineering controls

This product must not be handled in a confined space without adequate ventilation.

Eye/face protection

No specific eye protection required during normal use.

Hand protection

For prolonged or repeated skin contact use suitable protective gloves. (Household rubber gloves.)

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection

Respiratory protection not required.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance

Liquid.

Colour

Amber.

Odour

Characteristic. White spirit.

Melting point

-20°C

Initial boiling point and range

130°C @ 760 mm Hg

Flash point

38°C . Measured using test method, CC (Closed cup).

Vapour pressure

0.3 - 0.6 kPa @ °C

Relative density

0.900 @ 15°C

Solubility(ies)

Insoluble in water.

Auto-ignition temperature

250°C

9.2. Other information

Jangro - POLYURETHANE FLOOR SEAL

Other information

None.

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapours may form explosive mixtures with air.

10.2. Chemical stability

Stability

No particular stability concerns.

10.3. Possibility of hazardous reactions

See sections 10.1,10.4 & 10.5

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid

Oxidizing agents

10.6. Hazardous decomposition products

Thermal decomposition or combustion products may include the following substances: Oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects

We have not carried out any animal testing for this product. Any ATE figures quoted below are from Toxicity Classifications that have been carried out using ATE (Acute Toxicity Estimate) Calculation Method using LD50 or ATE figures provided by the Raw Material Manufacturer.

SECTION 12: Ecological Information

Ecotoxicity

Not regarded as dangerous for the environment.

12.1. Toxicity

We have not carried out any Aquatic testing, therefore we have no Aquatic Toxicity Data specifically for this product. The Aquatic Toxicity Data, where provided by the raw material manufacturer for ingredients with aquatic toxicity, can be made available on request.

12.2. Persistence and degradability

Persistence and degradability

The product is readily biodegradable.

12.3. Bioaccumulative potential

Not known

12.4. Mobility in soil

Mobility

Not known.

12.5. Results of PBT and vPvB assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Not known.

SECTION 13: Disposal considerations

Jangro - POLYURETHANE FLOOR SEAL**13.1. Waste treatment methods****Disposal methods**

Empty Container can be consigned to normal waste. Unwanted product must be sent for disposal by approved waste contractor.

SECTION 14: Transport information**14.1. UN number**

UN No. (ADR/RID)	1263
UN No. (IMDG)	1263
UN No. (ICAO)	1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID)	PAINT
Proper shipping name (IMDG)	PAINT
Proper shipping name (ICAO)	PAINT
Proper shipping name (ADN)	PAINT

14.3. Transport hazard class(es)

ADR/RID class	Class 3: Flammable liquids.
ADR/RID label	3
IMDG class	Class 3: Flammable liquids.
ICAO class/division	Class 3: Flammable liquids.

Transport labels**14.4. Packing group**

ADR/RID packing group	III
IMDG packing group	III
ICAO packing group	III

14.5. Environmental hazards**14.6. Special precautions for user**

EmS	F-E, S-E
Emergency Action Code	
Hazard Identification Number (ADR/RID)	
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not relevant. for a packaged product.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU legislation**

Safety Data Sheet prepared in accordance with REACH Commission Regulation (EU) No 453/2010 (which amends Regulation (EC) No 1907/2006). The product is as classified under GHS/CLP- Regulation (EC) No 1272/2008 classification, labelling & packaging of substances & mixtures. Ingredients are listed with classification under both CHIP - Directive 67/548/EEC - classification, packaging & labelling of dangerous substances & GHS/CLP- Regulation (EC) No 1272/2008 classification,

Jangro - POLYURETHANE FLOOR SEAL

labelling & packaging of substances & mixtures.

Guidance

Workplace Exposure Limits EH40.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out as not applicable as this product is a mixture.

SECTION 16: Other information

Key literature references and sources for data

Material Safety Data Sheet, Misc. manufacturers. CLP Class - Table 3.1 List of harmonised classification and labeling of hazardous substances. CHIP Class - Table 3.2 The list of harmonised classification and labelling of hazardous substances from Annex I to Directive 67/548/EEC. ECHA - C&L Inventory database.

Revision comments

This product is now using classification from GHS/CLP - Regulation (EC) No 1272/2008 classification, labelling & packaging of substances & mixtures.

Revision date 01/06/2015

Revision Issue 7

SDS status The Risk Phrases / Hazard Statements listed below in this Section No 16 relate to the Raw Materials (Ingredients) in the Product (as listed in Section 3) and NOT the product itself. For the Risk Phrases / Hazard Statements relating to this Product see Section 2.

Risk phrases in full

R10 Flammable.
R65 Harmful: may cause lung damage if swallowed.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

Hazard statements in full

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.